

# DP 36 SF EVO

**BEST PRACTICE**  
TOURING



Product name	DP 36 SF EVO
Product code LH Version	36SFEV.00005
Product code RH Version	36SFEV.00006
Product code LH Version*	36SFEV.00007
Square drive	1/2"
Weight	2,23 kg (4.9 lbs)
Length	161 mm (6.3")
Air inlet	LH / RH 3/8" BSP LH* 1/4" NPT
Supply hose inside diameter	13 mm (0.51")
Max pressure	14 bar (200 psi)
Free Speed (14 bar / 200 psi)	LH / RH 14500 rpm LH* 15000 rpm
Max torque	LH / RH 850 Nm (626 ft-lbs) LH* 900 Nm (663 ft-lbs)
Gun selector plate	2 port

\*US VERSION

WEIGHT 2,23 kg (4.9 lbs)  
MAX TORQUE 900 Nm (663 ft-lbs)  
AIR INLET 3/8" BSP

- New carbon vanes
- Developed for 5 nuts
- Additional air exhausts to increase the speed

HIGHLIGHTS

## DP 36 SF EVO LH



The fast left hand version (blue) loosens nuts tightened clockwise faster

## DP 36 SF EVO RH



The fast right hand version (red) loosens nuts tightened anticlockwise faster

AVAILABLE VERSIONS

6 NEW CARBON VANES INSIDE

TWIN HAMMER MECHANISM

BUILT-IN FRS

AERONAUTICAL ALUMINIUM FRONT COVER



**VERY FAST!**

Wheel gun for 5 nuts wheels  
(touring) application!

SUGGESTED COUPLINGS & FITTINGS

- couplings: minimal bore of 7,6 mm (19/64")
- male 3/8" BSP fittings (UE version)  
1/4" NPT fittings (US version)



Operating and maintenance manual  
**DP 36 SF EVO**



WWW.PAOLI.NET | SALES@PAOLI.NET | +39.0522.364511