



DP 36 SF EVO



BEST PRACTICE

TOURING CARS

Product name	DP 36 SF EVO
Product code LH Version	36SFEV.00005
Product code RH Version	36SFEV.00006
Product code UH Version	36SFEV.00007
Square drive	1/2"
Weight	2,23 kg (4.9 lbs)
Length	161 mm (6.3")
Air inlet	LH / RH 3/8" BSP LH* 1/4" NPT
Supply hose inside diameter	13 mm (0.51")
Max pressure	14 bar (200 psi)
Free Speed (14 bar / 200 psi)	LH / RH 14500 rpm LH* 15000 rpm
Max torque	LH / RH 850 Nm (626 ft-lbs) LH* 900 Nm (663 ft-lbs)
Gun selector plate	2 port

*US VERSION

AVAILABLE VERSIONS



Fast left hand version:
loosens nuts tightened
clockwise faster



Fast right hand version:
loosens nuts tightened
anticlockwise faster

HIGHLIGHTS

- New carbon vanes
- Developed for 5 nuts
- Additional air exhausts to increase the speed

VERY FAST!

WHEEL GUN FOR 5 NUTS WHEELS
(TOURING) APPLICATION!

6 NEW CARBON VANES INSIDE

BUILT-IN FRS

TWIN HAMMER MECHANISM

AEROSPACE ALUMINIUM
FRONT COVER

SUGGESTED COUPLINGS & FITTINGS

- Couplings: minimal bore of 7,6 mm (19/64")
- Male 3/8" BSP fittings (UE version)
1/4" NPT fittings (US version)

MANUAL



Operating and
Maintenance
Manual



WWW.PAOLI.NET | SALES@PAOLI.NET | +39.0522.364511