



DP 4000 30BAR

BEST PRACTICE

ENDURANCE / GT

Product name	DP 4000 30BAR
Front Cover Type	AEROSPACE 7075 ALUMINIUM ALLOY
Product code LH Version	400030.00013
Product code RH Version	400030.00014
Product code UH Version	400030.00015
Square drive	1"
Weight	3,97 kg (8.7 lbs)
Length	193 mm (7.59")
Air inlet	3/8" BSP
Supply hose inside diameter	13 mm (0.51")
Max pressure	30 bar (435 psi)
Free Speed (25 bar / 362 psi)	LH / RH / UH 15500 rpm
Max torque	LH / RH 3800 Nm (2810 ft-lbs) UH 3500 Nm (2590 ft-lbs)
Gun selector plate	3 port (2 port available on demand)

ALSO AVAILABLE

Product name	DP 4000 30BAR
Front Cover Type	CARBON COVER
Product code LH Version	400030.00016
Product code RH Version	400030.00017
Product code UH Version	400030.00018
Weight	3,90 kg (8.6 lbs)

AVAILABLE VERSIONS



Fast left hand version:
loosens nuts tightened
clockwise faster



Fast right hand version:
loosens nuts tightened
anticlockwise faster



Special unhanded version:
loosens at same speed both
the nuts tightened clockwise
and anticlockwise

HIGHLIGHTS


- Optional front cover made of carbon
- New carbon peek vane

- 30 BAR DYNAMIC RESISTANT
- INCREASED POWER
- VERY TOUGH MATERIALS AND TECHNICAL SOLUTIONS APPLIED

NEW OPTIONAL MONOLITHIC PIN



AEROSPACE ALUMINIUM FRONT COVER



SPLINE DRIVE READY

NEW RADIAL HAMMER MECHANISM (RHM) INSIDE!

The new radial hammer mechanism guarantees a superior performance and a longer lifespan of the hammer mechanism parts, thanks to the new developed geometry.



NEW OPTIONAL! TO INCREASE DURABILITY AND STRENGTH

BUILT-IN FRS

STANDARD DOUBLE STAGE TRIGGER

SUGGESTED COUPLINGS & FITTINGS

- Couplings: minimal bore of 10 mm (25/64")
- Male 1/2" BSP fittings

MANUAL



Operating and
Maintenance
Manual



WWW.PAOLI.NET | SALES@PAOLI.NET | +39.0522.364511