

SUPERSPORT



BEST PRACTICE

NASCAR CUP SERIES
GT-ENDURANCE



Product name	SUPERSPORT
Product code LH Version	SUPERSPORT.01
Product code RH Version	SUPERSPORT.02
Product code UH Version	SUPERSPORT.03
Drive shaft	Spline Drive
Weight	4,03 kg (8.9 lbs)
Length	202 mm (7.95")
Air inlet	3/8" BSP
Supply hose inside diameter	13 mm (0.51")
Max pressure	25 bar (362 psi)
Free Speed (25 bar / 362 psi)	LH / RH 11500 rpm UH 11000 rpm
Max torque	LH / RH 3500 Nm (2590 ft-lbs) UH 2800 Nm (2065 ft-lbs)
Gun selector plate	2 port

ALSO AVAILABLE

Product name	SUPERSPORT SQUARE DRIVE
Drive shaft	Square Drive
Product code LH Version	SUPERSPORT.04
Product code RH Version	SUPERSPORT.05
Product code UH Version	SUPERSPORT.06

AVAILABLE VERSIONS


LH Fast left hand version: loosens nuts tightened clockwise faster

RH Fast right hand version: loosens nuts tightened anticlockwise faster

UH Special unhandled version: loosens at same speed both the nuts tightened clockwise and anticlockwise

HIGHLIGHTS

- Radial Hammer Mechanism



NEW FAST REVERSE SYSTEM

Longer and easier to move. Positioned on the side where the rotation reverse mechanism turns from loosening to tightening.

BUILT-IN FRS

SUGGESTED COUPLINGS & FITTINGS

- couplings: minimal bore of 10 mm (25/64")
- Inlet made by steel

NEW RADIAL HAMMER MECHANISM (RHM) INSIDE!

The new radial hammer mechanism guarantees a superior performance and a longer lifespan of the hammer mechanism parts, thanks to the new developed geometry.



ALREADY INCLUDED!
TO INCREASE DURABILITY AND STRENGTH

MANUAL



Operating and Maintenance Manual

