



SUPERSPORT



BEST PRACTICE

NASCAR CUP SERIES
GT-ENDURANCE

Product name	SUPERSPORT
Product code LH Version	SUPERSPORT.01
Product code RH Version	SUPERSPORT.02
Product code UH Version	SUPERSPORT.03
Drive shaft	Spline Drive
Weight	4,03 kg (8.9 lbs)
Length	202 mm (7.95")
Air inlet	3/8" BSP
Supply hose inside diameter	13 mm (0.51")
Max pressure	25 bar (362 psi)
Free Speed (25 bar / 362 psi)	LH / RH 11500 rpm UH 11000 rpm
Max torque	LH / RH 3500 Nm (2590 ft-lbs) UH 2800 Nm (2065 ft-lbs)
Gun selector plate	2 port
ALSO AVAILABLE	
Product name	SUPERSPORT SQUARE DRIVE
Drive shaft	
Product code LH Version	SUPERSPORT.04
Product code RH Version	SUPERSPORT.05
Product code UH Version	SUPERSPORT.06

AVAILABLE VERSIONS



Fast left hand version:
loosens nuts tightened
clockwise faster



Fast right hand version:
loosens nuts tightened
anticlockwise faster



Special unhanded version:
loosens at same speed both
the nuts tightened clockwise
and anticlockwise

HIGHLIGHTS

- Radial Hammer Mechanism

NEW FRONT COVER SHAPE

AEROSPACE ALUMINIUM
FRONT COVER



NEW OPTIONAL
MONOLITHIC PIN



NEW FAST REVERSE SYSTEM

Longer and easier to move.
Positioned on the side where
the rotation reverse mechanism
turns from loosening to
tightening.



SQU
READY

NEW RADIAL HAMMER
MECHANISM (RHM) INSIDE!

The new radial hammer mechanism guarantees a
superior performance and a longer lifespan of the
hammer mechanism parts, thanks to the new devel-
oped geometry.

BUILT-IN FRS



ALREADY INCLUDED!
TO INCREASE DURABILITY AND STRENGTH

SUGGESTED COUPLINGS & FITTINGS

- couplings: minimal bore of 10 mm (25/64")
- Inlet made by steel

MANUAL



Operating and
Maintenance
Manual



WWW.PAOLI.NET | SALES@PAOLI.NET | +39.0522.364511