

TORQUE WRENCHES

DIGITAL TORQUE WRENCHES CHIAVI DINAMOMETRICHE DIGITALI

FEATURES

- Torque accuracy: $\pm 2\%$
- Torque/Angle accuracy: $\pm 2\%$
- Peak hold and track mode direct readings.
- Tolerance range adjustment both on torque and angle.
- User tightening sets definition.
- Optical signals through 3 leds, and acoustical signal with buzzer.
- Clockwise and anticlockwise (CW and CCW) readings.
- Memory up to 900 values.
- Angle and Torque Preset.
- Auto switch-off.
- N-m, Kg m, Lbf in, Lbf ft.



CARATTERISTICHE

- Precisione della coppia: $\pm 2\%$
- Precisione coppia/angolo: $\pm 2\%$
- Peak hold e track mode letture dirette.
- Regolazione dell'intervallo di tolleranza sia sulla coppia che sull'angolo.
- Il serraggio utente definisce la definizione.
- Segnali ottici tramite 3 led e segnale acustico con buzzer.
- Letture in senso orario e antiorario (CW e CCW).
- Memoria fino a 900 valori.
- Impostazione Angolo e Coppia.
- Spegnimento automatico.
- N-m, Kg m, Lbf in, Lbf ft.

Product Name Nome prodotto	23000-DGT	2600-DGT	2400-DGT
Product code Codice prodotto	B.35.0002	B.35.0003	B.35.0004
Capacity (Nm) Capacità (Nm)	100-1000 Nm	80-800 Nm	20-200 Nm
Drive Attacco	1"	3/4"	1/2"
Length Lunghezza	52.7 in 1340 mm	43.3 in 1100 mm	20.1 in 512 mm
Weight Peso	14.5 lbs 6,60 kg	9.7 lbs 4,40 Kg	2.7 lbs 1,25 kg
Accessories Accessori	USB data transfer kit (Product code: B.35.0011 Kit USB per trasferimento dati (Codice prodotto: B.35.0011)		

CHIAVI DINAMOMETRICHE

TORQUE WRENCHES WITH RATCHET CHIAVI DINAMOMETRICHE A CRICCHETTO



FEATURES

- Fast and easy setting.
- Long life accuracy and repeatability.
- Ergonomic handle.
- With graduated scale in N-m and Lbf.ft.
- Dual signal when the set torque is reached: acoustical click and effort decrease.
- Guaranteed accuracy $\pm 3\%$ in accordance with EN ISO 6789:2003.

CARATTERISTICHE

- Impostazione facile e veloce.
- Precisione e ripetibilità di lunga durata.
- Impugnatura ergonomica.
- Con scala graduata in N-m e Lbf.ft.
- Doppio segnale al raggiungimento della coppia impostata: scatto acustico e diminuzione dello sforzo.
- Precisione garantita $\pm 3\%$ secondo EN ISO 6789:2003.

Product Name Nome prodotto	300	330	350
Product code Codice prodotto	B.35.0008	B.35.0009	B.35.0010
Capacity (Nm) Capacità (Nm)	40-200 Nm 30-150 lbf.ft	160-800 Nm 120-590 lbf.ft	200-1000 Nm 150-750 lbf.ft
<input type="checkbox"/>	1/2"	3/4"	3/4"
Length Lunghezza	450 mm	1180 mm	1340 mm
Weight Peso	1,20 kg	6,70 kg	7,40 kg

DIAL TORQUE WRENCHES CHIAVI DINAMOMETRICHE ANALOGICHE



FEATURES

- Left and right hand use.
- Precise tightening achieved by the torsion bar system.
- The small head allows torque application even in narrow areas.
- Reading scale in Nm/Lbf.in or Nm/Lbf.ft.
- Accuracy $\pm 4\%$.
- Traceable calibration certificate through accredited laboratories.

CARATTERISTICHE

- Uso con mano destra e sinistra.
- Serraggio preciso ottenuto con il sistema a barra di torsione.
- La testa piccola permette l'applicazione della coppia anche in aree strette.
- Scala di lettura in Nm/Lbf.in o Nm/Lbf.ft.
- Precisione 4%.
- Certificato di taratura tracciabile tramite laboratori accreditati.

Product Name Nome prodotto	7000	800	700
Product code Codice prodotto	B.35.0005	B.35.0006	B.35.0007
Capacity (Nm) Capacità (Nm)	300-1500	80-400	40-200
STEP	20 Nm	5 Nm	2,5 Nm
<input type="checkbox"/>	1"	1/2"	1/2"
Length Lunghezza	1956 mm (including extension)	559 mm	559 mm
Weight Peso	9,072 kg	1,361 kg	1,361 kg